




PORTABLE SAW MACHINES







AVAILABLE BLADES



TECHNICAL CHARACTERISTICS



PACKAGE



- For cutting porcelain, single-double fired, marble, granite.
- Straight, 45° bevel (Jolly) cuts, square e round knockouts, sanding/polishing.
- Unlimited size of cut.
- Maximum thickness of cut: 25 mm (1") in single pass; 50 mm (2") in double pass.
- Maximum disc: Ø 115 mm (4 1/2"); smallest blade: Ø 100 mm (4").
- Gear ratio of motor to disc 1 ÷ 2.1. Drive belt type Z90.
- The blade is cooled via heavy duty pump.
- Supplied with: turbo blade Ø 100 mm (4") for tiles, 5 abrasive discs for polishing/sanding, key kit, dressing stone, user and maintenance manual.
- Turtle shell cover helps to prevent damage when not in use.

MODEL SPECIFICATIONS

| Part No. | Barcode | Box | Lightning Bolt | M | Motor | Motor | Disc | Disc | |
|-------------------|---------------|-----|----------------|--------------|------------------|-------|--------|------|------|
| 125INOX F | 8024648003584 | 1 | 230 V 50 Hz | single-phase | 0,9 HP / 0,66 kW | 2800 | 100 mm | 4" | 5800 |
| 125INOX 60 | 8024648017055 | 1 | 230 V 60 Hz | single-phase | 0,9 HP / 0,66 kW | 3360 | 100 mm | 4" | 7000 |
| 125INOX US | 8024648009265 | 1 | 110 V 60 Hz | single-phase | 0,9 HP / 0,66 kW | 3360 | 100 mm | 4" | 7000 |
| 125INOX GB | 8024648009258 | 1 | 110 V 50 Hz | single-phase | 0,9 HP / 0,66 kW | 2800 | 100 mm | 4" | 5800 |

CUTTING SPECIFICATIONS AND MACHINE DIMENSIONS/WEIGHT

| Model | Disc | Blade | Blade | Blade | Blade | Blade | Machine | Weight | Box | Weight |
|-------------|--------|--------|-------|-------|-------|-------|--------------------------------|-----------------|-------------------------------|-----------------|
| GS86 | 100 mm | 4" | 18 mm | 3/8" | 17 mm | 3/8" | 45x45xh 30 cm 18"x18"xh 12" | 25 Kg 55 lbs | 50x50xh 35 cm 20"x20"xh 13 | 26 Kg 57 lbs |
| | 115 mm | 4 1/2" | 25 mm | 1" | 17 mm | 3/8" | | | | |

